



FIRE DOORS

- The range of Hume fire rated doors is fully tested and approved in accordance with Australian Standard AS 1905.1 with testing and certification by the CSIRO.
- All doors are supplied with metal reinforcing plates as standard, with provision for 3 hinges, an automatic closer and a lock. (Match with fire door frames refer to page 45)
- Fire door core material is a monolithic vermiculite (no asbestos).
- Hume Doors also supplies fire doors with vision panels, and for pairs of doors we offer aluminium T Bar meeting stiles, aluminium bullnose meeting stiles as well as the option of 2 way swing doors (double action). **Pairs of doors must be 45mm thick and must be ordered as pairs.**

Before installation please refer to our certification list including approved hardware.

For certification and tags to suit doors please contact your Hume State Office.



FIRE DOORS

- 1 Hour
- 2 Hour
- 3 Hour
- 4 Hour



GLAZED PANELS

- Suit Firedoors
- Panel Sizes:
600x100, 300x200
or 450x120

MINI FIRE DOORS - NOMINAL 35MM THICK

	1 hour	1 hour	1 hour	2 hour	2 hour
	MDF	Ply	Tempered Hardboard	Ply	Tempered Hardboard
Standard Sizes	37mm	36mm	35mm	36mm	35mm
2040x820	367	411	433	456	442
2040x870	439	483	505	528	515
2040x920	467	522	544	567	556
Special Size up to:					
2050x820	428	473	495	516	503
2100x920	502	556	577	599	589
2100x1200	611	667	700	721	707
2400x920	622	644	665	754	743
2400x1200	665	734	755	810	797

MAXI FIRE DOORS - NOMINAL 45MM THICK

	1 hour	1 hour	1 hour	2 hour	2 hour	3 hour	4 hours
	MDF	Ply	Tempered Hardboard	Ply	Tempered Hardboard	Ply	Ply
Standard Sizes	47mm	46mm	45mm	46mm	45mm	45mm	45mm
2040x820	399	444	467	488	476	512	533
2040x870	466	511	533	555	542	589	622
2040x920	488	533	555	577	564	601	633
Special Size up to:							
2050x820	467	512	533	556	542		
2100x920	523	577	611	622	608	644	677
2100x1200	622	688	711	734	720	742	776
2400x920	644	667	688	777	764	734	766
2400x1200	711	761	777	831	820	853	886

Extra cost options

Robax Vision Panels 600x100, 300x200 or 450x120	P.O.A.	Additional
T-bar including intumescent seal to form pairs 2100mm long	257	Additional
T-bar including intumescent seal to form pairs 2400mm long	322	Additional
Tags	11	Per door
Certification	P.O.A.	
Metal Clad and Capping	P.O.A.	