

FIRE DOORS

- TVC Firecore available in 1, 2, 3 and 4 hour ratings.
- Face Materials: MDF, Ply or Tempered Hardboard.
- Fire doors are supplied with metal reinforcing plates as standard with provisions for 3 hinges, an automatic closer and a lock.
- Match with fire rated steel door frames.
- Fire doors are available with Vision Panels, Cladding and Air Grilles.
- Hume fire rated doors are tested and approved in accordance with Australian Standards.
- Refer to our approved fire rated hardware list before installation. Contact your Hume branch for compliance information.



FIRE DOOR CONSTRUCTION

- Metal Inner Plates for Hinges, Lock and Closer
- Fire door core material is made from a monolithic vermiculite



ROBAX VISION PANEL

- Sizes: 600x100, 300x200, 450x120



FIRE DOOR PAIRS

- Only Maxi Fire Doors are available for pairs
- Doors must be 45-47mm thick and must be ordered as pairs
- Aluminium T-Bar meeting stiles
- Aluminium bullnose meeting stiles
- 2 way swing doors (double action)

ADDITIONAL EXTRAS

Robax Vision Panels	600x100, 300x200 or 450x120	P.O.A.
T-bar including intumescent seal	Pairs 2100mm long	Additional P.O.A.
T-bar including intumescent seal	Pairs 2400mm long	Additional P.O.A.
Fire Door Tags		P.O.A. per door
Letter of compliance		P.O.A.
Metal Clad and Capping		P.O.A.

FOR PRICING EMAIL OUR ESTIMATING TEAM

✉ estimating@humedoors.com.au

**NEW FIRE DOOR STANDARDS
COMING IN 2022**

For more information contact your sales representative